

EZ-4719-B DUCT SEALANT

The EZ-4719-B is a flammable solvent based product used for sealing air conditioning and heating ducts. It has the same general composition as our EZ-6010 but with a higher viscosity level. The EZ-4719-B is a U.L. Listed premium grade duct sealant.



APPLICATIONS

- Sealing sheet metal joints and seams in high or low pressure duct systems.
- Making air and water tight all types of galvanized, aluminum or stainless steel sheet metal seams.
- Sealing off sheet metal screw and rivet heads.
- Adhering butted fiberglass duct liner joints to prevent edge pickup by high velocity air.
- Sealing and seaming air systems as used in dryers, air conditioners, etc.

ADVANTAGES

- Forms a tough air tight and water tight seal.
- Flexes with expansion and contraction of the sheet metal.
- Can be applied quickly by caulking gun, putty knife, trowel or heavy brush.
- Bonds to galvanized, stainless steel or aluminum.
- Adds structural strength to the flange or seam.

PROPERTIES

Composition:	An oil and water resistant rubber compound which cures into a tough flexible seal. It bonds very well to galvanized, stainless steel or aluminum sheet metal. Once cured it will not flow out of the sealed flange under pressure, but will flex with expansion and contraction.
Color:	Reddish brown
Viscosity:	100,000 cp. to 150,000 cp.
Solids:	~41%
Solvents:	Ketones
Storability:	6 months in tightly closed containers
Service Temperature:	-20°F to 200°F
Application and Storage:	60°F to 80°F
Weight per Gallon:	
Application Techniques:	Caulk gun, putty knife, trowel or heavy brush
Tack Time:	Tack free for 5 minutes. Full cure 1 to 3 days
Open Time:	
Flammability:	Wet – Flammable. Dry – Slow burning
Coverage Per Gallon:	1/8" bead - 150 linear feet 1/4" bead - 37 linear feet

Not recommended for exposed outdoor use

Color



Application Methods

